itc · MULTIFUNCTION LOUDSPEAKERS

KS-12A25

Portable Active Column Speaker

The itc KS-12A25 is a portable Active Column Speaker from itc's Multifunction Loudspeakers range, built for speech and music reinforcement in conference rooms, banquet halls, theatres, KTV and multipurpose venues.

Key figures: rated power 400W+400W; peak power 1600W+1600W; crossover frequency 4th/200Hz, DSP electronic frequency division. Highlights include 12-inch Subwoofer, eight 2.3-inch Mid-High Drivers and active Portable Line Array System.



Key features

- 12-inch Subwoofer — Dual-guided enclosure with low-frequency response down to 38Hz Delivers powerful, deep, and impactful bass performance
- Eight 2.3-inch Mid-High Drivers — Achieves high-definition, seamless audio coverage across the venue Ensures optimal listening experience for all audience positions
- Active Portable Line Array System — Supports Bluetooth TWS wireless pairing and multi-channel inputs (XLR Combo & RCA) Built-in DSP processor with physical buttons for one-touch bass boost and noise reduction Aluminum alloy

Technical specifications

Type	Active portable column speaker
Rated power	400W+400W
Peak power	1600W+1600W
Crossover frequency	4th/200Hz, DSP electronic frequency division
Frequency range (-3dB)	38 Hz-20KHz
Input method	2-channel XLR multi-function jack input, 1-channel stereo RCA input, 1-channel Bluetooth input, 1-way XLR output
Functional support	Support low frequency enhancement, Bluetooth supports TWS, and supports one-key noise reduction
Maximum sound pressure level (rated/peak	1 17 dB/12 3 dB
Voltage input	AC 220V 50Hz-60Hz
Coverage	1 2 0° □H□ 40° □V□
Low frequency speaker	12″ × 1
Mid-high frequency speakers	2.3 ” × 8
Net weight	17.5kg
Dimensions (H x W x D)	Bass: 560 × 350 × 430 (mm) Sound column: 597 × 96 × 103 (mm) Support rod: 1015×35×50□mm□
Total product height	2000 (mm)