itc · DIGITAL CONFERENCE SYSTEMS

TS-0302/TS-0302A

Chairman Unit/Delegate Unit

The itc TS-0302/TS-0302A is a chairman Unit/Delegate Unit from itc's Digital Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz-16kHz; sensitivity -41±1.5dBV/Pa. Highlights include and digital transmission link.



Key features

-
- The core components of the microphone all use domestic chips — The core components of the microphone all use domestic chips, which are safe and confidential.
- Digital transmission link — Digital transmission link, connected to conference controller cascade port for power supply through network port to six-core aviation cable; uncompressed audio transmission technology, 48K sampling rate,
- The use of capacitive touch buttons can effectively… — The use of capacitive touch buttons can effectively eliminate the noise of button knocking and ensure a good venue environment.
- Built-in high-fidelity speaker with volume adjustment and… — Built-in high-fidelity speaker with volume adjustment and howling suppression function. When the microphone is turned on, the built-in speaker will be automatically turned

Technical specifications

Microphone type	Cardioid Electret Microphone
Frequency response	80Hz-16kHz
Input impedance	680Ω
Sensitivity	-41±1.5dBV/Pa
Maximum SPL	120dB
SNR	>80dB(A)
Dynamic range	>80dB
THD	<0. 1 %
Power consumption	4W
Headphone load	16-32Ω
Headphone jack	3.5mm
Speaker	Built-in 1 4Ω 2W speaker
Network port	2 cascade network port s
Power supply	Powered by conference controller
Color	Graphite gray
Sign in function	Touch button sign in
Installation method	Desktop installation

Continued specifications on request.