itc · DIGITAL CONFERENCE SYSTEMS

TS-0308/TS-0308A

Conference Chairman Unit

The itc TS-0308/TS-0308A is a conference Chairman Unit from itc's Digital Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz~16KHz; sensitivity - 41 ± 1.5 dB(0dB=1V/Pa,at1KHz). Highlights include digital transmission link.



Key features

- Digital transmission link — Digital transmission link, connected to the cascade port of the conference server for power supply through the network port to six-pin aviation cable, uncompressed audio transmission technology, 48K sampling
- The capacitive touch buttons can effectively eliminate the… — The capacitive touch buttons can effectively eliminate the button tapping noise and ensure a good venue environment.
- Support PC software microphone control and voice control… — Support PC software microphone control and voice control function.
- The chairman unit has the priority to turn off the speaking… — The chairman unit has the priority to turn off the speaking delegate unit.
- Support TCP/IP protocol cluster — Support TCP/IP protocol cluster, support ICMP, HTTP, UDP, TCP, IGMP and other protocols.

Technical specifications

Microphone type	Electret condenser microphone
Microphone directi vity	Cardioid
Frequency response	80Hz~16KHz
Microphone input impedance	680 Ω
Sensitivity	- 41 ± 1.5 dB(0dB=1V/Pa,at1KHz)
Maximum SPL	120dB
SNR	>80dB(A)
Crosstalk	>70dB
Dynamic range	>80dB
THD	<0.3%
Maximum power consumption	2W
Network port	2, cascaded network ports
Power supply	Conference server power supply
Color	Gray
Dimension	113 × 100 × 36mm (L×W×H) (excluding the length of the microphone pole)
Microphone pole	380mm black

Continued specifications on request.