itc · DIGITAL CONFERENCE SYSTEMS

TS-0309

Conference Chairman Unit

The itc TS-0309 is a conference Chairman Unit from itc's Digital Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz~16KHz; sensitivity -41±1.5dB(0dB=1V/Pa,at1KHz). Highlights include uncompressed audio transmission technology, adopt 100M network transmission and adopt standard TCP/IP communication protocol.



Key features

- The capacitive touch buttons can effectively eliminate the… — The capacitive touch buttons can effectively eliminate the button tapping noise and ensure a good venue environment.
- Uncompressed audio transmission technology — Uncompressed audio transmission technology, 48K sampling rate, 80Hz-16KHz bandwidth perfect sound quality.
- Adopt 100M network transmission — Adopt 100M network transmission, adopt network cable hand-in-hand connection, convenient for wiring.
- Adopt standard TCP/IP communication protocol — Adopt standard TCP/IP communication protocol, support ping packet function.
- Adopt a 3.5-inch full color touch screen

Technical specifications

Microphone type	Cardioid Electret
Microphone directivity	Cardioid
Frequency response	80Hz~16KHz
Microphone input impedance	680Ω
Sensitivity	-41±1.5dB(0dB=1V/Pa,at1KHz)
Maximum SPL	120dB
SNR	>80dB(A)
Crosstalk	>70dB
Dynamic range	>80dB
THD	<0.1%
Maximum power consumption	4.5W
Power supply	Conference server power supply