itc · WIRELESS CONFERENCE SYSTEMS

TS-0310A

Conference Delegate Unit

The itc TS-0310A is a conference Delegate Unit from itc's Wireless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz~16KHz; sensitivity - 41 ±1.5dB (0dB=1V/Pa,at 1KHz). Highlights include uncompressed audio transmission technology, adopt 100M network transmission and adopt standard TCP/IP communication protocol.



Key features

- The capacitive touch buttons can effectively eliminate the… — The capacitive touch buttons can effectively eliminate the button tapping noise and ensure a good venue environment.
- Uncompressed audio transmission technology — Uncompressed audio transmission technology, 48K sampling rate, 80Hz-16KHz bandwidth perfect sound quality.
- Adopt 100M network transmission — Adopt 100M network transmission, adopt network cable hand-in-hand connection, convenient for wiring.
- Adopt standard TCP/IP communication protocol — Adopt standard TCP/IP communication protocol, support ping packet function.
- Adopt a 4.3-inch full color touch screen

Technical specifications

Model	TS-0310A
Microphone type	Electret condenser microphone
Microphone directivity	Cardioid
Frequency response	80Hz~16KHz
Microphone input impedance	680 Ω
Sensitivity	- 41 ±1.5dB (0dB=1V/Pa,at 1KHz)
Maximum SPL	120dB(THD>3%)
S NR	>80dB(A)
Crosstalk	>70dB
Dynamic range	>80dB
THD	<0.1%
Maximum power consumption	3W
Power supply	Conference server power supply
Color	Fine sand graphite gray
Sign-in method	Key sign in
Dimension	140*136*49mm (L*W*H)
Microphone pole	380mm

Continued specifications on request.