itc · DIGITAL CONFERENCE SYSTEMS

TS-0311A

Conference Microphone

The itc TS-0311A is a conference Microphone from itc's Digital Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz~16KHz; sensitivity - 41 ±1.5dB (0dB=1V/Pa,at 1KHz). Highlights include digital transmission link and the chairman unit has a priority function.



Key features

- All core components of the microphone use domestically… — All core components of the microphone use domestically produced chips, which are safe, confidential and controllable.
- Digital transmission link — Digital transmission link, connected to the cascade port of the conference server for power supply through the network port to six-pin aviation cable, uncompressed audio transmission technology, 48K sampling
- Physical silicone buttons are used to retain the feel of… — Physical silicone buttons are used to retain the feel of physical buttons while eliminating the clicking sound of physical buttons, ensuring a good venue environment.
- The chairman unit has a priority function — The chairman unit has a priority function, which can turn off the microphones of all delegate unit who are speaking.
- The conference PC software supports the function of timing… — The conference PC software supports the function of timing and scheduled speech for the delegate unit. The conference PC software supports the function of timing speech

Technical specifications

Microphone Type	Cardioid electret
Frequency response	80Hz~16KHz
Microphone input impedance	680Ω
Sensitivity	- 41 ±1.5dB (0dB=1V/Pa,at 1KHz)
Maximum SPL	120 dB
Crosstalk	>70dB
SNR	>80dB(A)
Dynamic Range	>80dB
THD	< 0.1 %
Maximum power consumption	2W
Power supply	Host power supply
Network port	2, hand-in-hand level cascade ports
Color	Graphite Gray
Installation	Desktop
Microphone rod length and color	409mm black (5-core cable)
Dimensions (L×W×H)	133.8 × 104.6 × 37.2 mm

Continued specifications on request.