**itc · DIGITAL CONFERENCE SYSTEMS**

# TS-0311D

Conference Microphone

The itc TS-0311D is a conference Microphone from itc's Digital Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz~16KHz; sensitivity - 40 ± 2 dB (0dB=1V/Pa,at 1KHz). Highlights include digital transmission link and the chairman unit has a priority function.



## Key features

- All core components of the microphone use domestically… — All core components of the microphone use domestically produced chips, which are safe, confidential and controllable.
- Digital transmission link — Digital transmission link, connected to the cascade port of the conference server for power supply through the network port to six-pin aviation cable, uncompressed audio transmission technology, 48K sampling
- Physical silicone buttons are used to retain the feel of… — Physical silicone buttons are used to retain the feel of physical buttons while eliminating the clicking sound of physical buttons, ensuring a good venue environment.
- The chairman unit has a priority function — The chairman unit has a priority function, which can turn off the microphones of all delegate unit who are speaking.
- The conference PC software supports the function of timing… — The conference PC software supports the function of timing and scheduled speech for the delegate unit. The conference PC software supports the function of timing speech

## Technical specifications

| | |
|---|---|
| Microphone Type | Cardioid electret |
| Frequency response | 80Hz~16KHz |
| Microphone input impedance | 1000 Ω |
| Sensitivity | - 40 ± 2 dB (0dB=1V/Pa,at 1KHz) |
| Maximum SPL | 1 20dB |
| SNR | >80dB(A) |
| Crosstalk | >70dB |
| Dynamic Range | >80dB |
| THD | < 0.1 % |
| Maximum power consumption | 2W |
| Power supply | Host power supply |
| Network port | 2, hand-in-hand cascade ports |
| Color | Graphite Gray |
| Installation | Desktop |
| Microphone rod length and color | 240mm integrated square short microphone rod (light black) |
| Dimensions (L×W×H) | 133.8 × 104.6 × 37.2mm (excluding microphone rod dimension ) |

Continued specifications on request.