itc · DIGITAL CONFERENCE SYSTEMS

TS-0318C/TS-0318CA

Conference Chairman/Delegate Unit

The itc TS-0318C family is a conference Chairman/Delegate Unit from itc's Digital Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres. It is offered in 2 versions — TS-0318C, TS-0318CA — so one design language covers rooms of different sizes.

Key figures: frequency response 80Hz~16KHz; sensitivity - 40±1dB (0dB=1V/Pa, at 1KHz). Highlights include adopt uncompressed audio transmission technology and adopt standard TCP/IP communication protocol.



Key features

- Short microphone pole design, long distance pickup
- Adopt uncompressed audio transmission technology — Adopt uncompressed audio transmission technology, 48K sampling rate, 80Hz-16KHz bandwidth perfect sound quality.
- Adopt 100M network transmission and single-line access to… — Adopt 100M network transmission and single-line access to the ring network to improve the reliability of system operation.
- Adopt standard TCP/IP communication protocol — Adopt standard TCP/IP communication protocol, and support ping packet function.
- Designed with a 4.1-inch circular full-color touch screen

Technical specifications

Versions: TS-0318C · TS-0318CA (values in the same order)

Microphone type	Electret condenser microphone
Microphone directivity	Cardioid
Frequency response	80Hz~16KHz
Input impedance	1KΩ
Sensitivity	- 40±1dB (0dB=1V/Pa, at 1KHz)
Max SPL	120dB(THD □ 3%)
SNR	>80dB(A)
Crosstalk	>70dB
Dynamic range	>80dB
THD	<0.1%
Max power consumption	4W
Power supply	Conference host power supply
Color	Fine sand graphite gray
Sign-in function	Key sign in
Installation method	Desktop
Microphone pole	240mm integrated square short microphone rod (light black)
Dimension (L×W×H)	100.9×130×54.3mm(base)

Continued specifications on request.