itc · DIGITAL CONFERENCE SYSTEMS

TS-0318E/TS-0318EA

Conference Chairman/Delegate Unit

The itc TS-0318E family is a conference Chairman/Delegate Unit from itc's Digital Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres. It is offered in 2 versions — TS-0318E, TS-0318EA — so one design language covers rooms of different sizes.

Key figures: frequency response 80Hz~16kHz; sensitivity -40 ± 1dB (0dB=1V/Pa, at 1KHz). Highlights include digital transmission link and support microphone control via PC software.



Key features

- Digital transmission link — Digital transmission link, connected to the cascade port of the conference controller for power supply through a network cable, uncompressed audio transmission technology, 48K sampling rate, 80Hz-16kHz
- Physical buttons to ensure reliable and stable triggering
- Support microphone control via PC software — Support microphone control via PC software, support voice control function.
- With 1 3.5mm headset interface can be used for recording... — With 1 3.5mm headset interface can be used for recording and connecting headphones.
- The chairman unit has the priority to turn off the delegate... — The chairman unit has the priority to turn off the delegate unit that is speaking.

Technical specifications

Versions: TS-0318E · TS-0318EA (values in the same order)

Microphone type	Electret Condenser Microphone
Microphone directivity	Cardioid
Frequency response	80Hz~16kHz
Input impedance	1K Ω
Sensitivity	-40 ± 1dB (0dB=1V/Pa, at 1KHz)
Max SPL	120dB(THD □ 3%)
SNR	>80dB(A)
Crosstalk	>70dB
Dynamic range	>80dB
THD	<0.1%
Maximum power consumption	2.5W
Power supply	Power ed by the conference controller
Color	Gray
Sign-in function	Button sign in
Installation method	Desktop installation
Dimension (L×W×H)	100.9 × 130 × 54.3mm (excluding the mic pole)

Continued specifications on request.