**itc · WIRELESS CONFERENCE SYSTEMS**

# TS-0326DA

Conference Microphone

The itc TS-0326DA is a conference Microphone from itc's Wireless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz~16KHz; sensitivity - 40 ± 2 dB (1KHz 0dB=1V/Pa); display screen LCD screen.



## Key features

- All core components of the microphone use domestic chips — All core components of the microphone use domestic chips, which are safe, confidential, and the core is controllable.
- It uses a 2.1-inch IPS full-color touch screen with a… — It uses a 2.1-inch IPS full-color touch screen with a simple interface.
- The microphone adopts a short microphone rod and a… — The microphone adopts a short microphone rod and a high-sensitivity microphone core design, which supports long-distance sound pickup.
- It adopts uncompressed audio transmission technology with a… — It adopts uncompressed audio transmission technology with a sampling rate of up to 48K, and can provide perfect sound quality with a bandwidth of 80Hz-16KHz.
- It adopts 100M network transmission — It adopts 100M network transmission, and the network connection uses network cables to facilitate wiring.

## Technical specifications

| | |
|---|---|
| Microphone type | Cardioid directional electret (gold-plated microphone core) |
| Frequency response | 80Hz~16KHz |
| Microphone input impedance | 680Ω |
| Sensitivity | - 40 ± 2 dB (1KHz 0dB=1V/Pa) |
| Maximum SPL | 1 20 dB(THD>3%) |
| Signal-to- noise ratio | >80dB(A) |
| Crosstalk | >70dB |
| Dynamic range | >80dB |
| THD | < 0.1 % |
| Maximum power consumption | 2.5 W |
| Color | Graphite Gray |
| Sign-in function | Physical silicone button sign in |
| Base size (L×W×H) | 126×105×54mm |
| Mic rod size | 240mm |
| Installation | Desktop |
| Weight | 0.84 Kg |

Continued specifications on request.