itc · DIGITAL CONFERENCE SYSTEMS

TS-0332/TS-0332A

Conference Microphone

The itc TS-0332 family is a conference Microphone from itc's Digital Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres. It is offered in 2 versions — TS-0332, TS-0332A — so one design language covers rooms of different sizes.

Key figures: frequency response 80Hz~16kHz; sensitivity -41±1.5dB (0dB=1V/Pa,at 1KHz). Highlights include embedded fully digital touch control design and digital transmission link.



Key features

- Embedded fully digital touch control design — Embedded fully digital touch control design, elegant and compact appearance, user-friendly operation.
- Digital transmission link — Digital transmission link, connected to the conference controller cascade port for power supply through network cable; uncompressed audio transmission technology, 48K sampling rate, 80Hz-16KHz bandwidth
- Capacitive touch keys are adopted to ensure no key tapping... — Capacitive touch keys are adopted to ensure no key tapping sound and a good environment of the venue.
- The unit supports microphone control and voice control... — The unit supports microphone control and voice control function by PC software.
- The chairman unit has the priority to turn off the delegate... — The chairman unit has the priority to turn off the delegate unit.

Technical specifications

Versions: TS-0332 · TS-0332A (values in the same order)

Microphone type	Cardioid Electret
Microphone directivity	Cardioid
Frequency response	80Hz~16kHz
Microphone input impedance	1KΩ
Sensitivity	-41±1.5dB (0dB=1V/Pa,at 1KHz)
Maximum SPL	120dB(THD>3%)
SNR	>80dB(A)
Crosstalk	>70dB
Dynamic range	>80dB
THD	<0.1%
MAX power consumption	2W
Power supply	Conference controller
Color	Graphite gray
Sign in	Key
Dimension (LxWxH)	108*77*129mm
Microphone rod	409mm black

Continued specifications on request.