itc · SIMULTANEOUS INTERPRETATION

TS-0370HYW

Translation Station

The itc TS-0370HYW is a translation Station from itc's Simultaneous Interpretation range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz~16KHz; sensitivity - 41 ±1.5dB (0dB=1V/Pa,at 1KHz). Highlights include it has an internal magnetic speaker.



Key features

- Adopting original clock synchronization and transmission... — Adopting original clock synchronization and transmission technology, audio delay is less than 5ms, sampling rate is 48K non-compressed audio transmission. Adopting Category
- It uses a 7 -inch touch color screen and the UI interface... — It uses a 7 -inch touch color screen and the UI interface is beautiful and elegant.
- It adopts a knob-type plug microphone rod with a two-color... — It adopts a knob-type plug microphone rod with a two-color indicator light, red for speaking .
- It has an internal magnetic speaker — It has an internal magnetic speaker, a headphone jack and a volume adjustment knob .
- Supports head-mounted microphone and boom microphone pickup

Technical specifications

Microphone type	Cardioid electret
Frequency response	80Hz~16KHz
Microphone input impedance	680Ω
Sensitivity	- 41 ±1.5dB (0dB=1V/Pa,at 1KHz)
Signal-to- noise ratio	>80dB(A)
Dynamic range	>80dB
THD	<0.01%
Maximum power consumption	4W
Power supply mode	Aviation power supply/DC power supply 36V
Color	black
Display	7- inch resistive touch screen
Dimensions (Lx Wx H)	268 × 16 2 × 66.5 mm (excluding microphone rod length)
Mic rod length	409mm
Installation	Desktop