itc · AUDIO PERIPHERALS

TS-3400MIX

Audio Processor

The itc TS-3400MIX is an audio Processor from itc's Audio Peripherals range, built for system integration — processing, feedback control, connectivity and wireless microphone distribution.

Key figures: main power supply 100-240AC/50-60Hz; static power consumption 3.3W; frequency response 80Hz ~ 16kHz. Highlights include precise frequency divider and built-in DANTE function of dual network ports.



Key features

- One 10" mid-woofer and one 1.4" compressed tweeter
- Precise frequency divider — Optimize the vocal MF performance
- Built-in DANTE function of dual network ports — Realize hand-in-hand connection
- High-quality and long-distance signal transmission
- With high-power amplifier modules and powerful audio processors — Support comprehensive parameter settings, including parameter equalization, frequency division, delay, and limit

Technical specifications

Simultaneous turned-on microphone	16 wired mics + 8 wireless mics
Frequency response	80Hz ~ 16kHz
SNR	> 75dB(A)
Dynamic range	>75dB(A)
THD	<0.05%
Main power supply	100-240AC/50-60Hz
Audio output	LINE OUT 1: 1V XLR balanced output ; LINE OUT 2: 1V RCA unbalanced output
Output load	>1KΩ
Static power consumption	3.3W
Connection method	RJ45 network port
Indicator light	AFC function indicator, audio signal indicator, working status indicator, power indicator
Working temperature	-10℃~+60℃
Working humidity	20%□80% relative humidity, no condensation
Weight	2.51kg
Dimension (L×W×H)	484×214×44mm
Installation method	19-inch standard cabinet