itc · WIRELESS CONFERENCE SYSTEMS

TS-3400MIXD

Audio Processor

The itc TS-3400MIXD is an audio Processor from itc's Wireless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz ~ 16kHz. Highlights include 3. The rear panel has 1 boat switch.



Key features

- It is a professional audio processor that is applicable to... — It is a professional audio processor that is applicable to digital conference systems. It supports intelligent mixing to solve the problem of howling when multiple microphones
- 1. With intelligent mixing and voice detection functions — 1. With intelligent mixing and voice detection functions, it can realize the simultaneous opening of 16 wired conference units + 8 wireless conference units and real-time detection
- 2. The product software is integrated with the digital... — 2. The product software is integrated with the digital conference host software, which can be used to configure the digital conference host and conference microphone
- 3. The rear panel has 1 boat switch — 3. The rear panel has 1 boat switch, 4 RJ45, 1 RS485, 2 RS232, 1 TYPE-Cinterface, 1 DIP switch, 1 XLR output interface and 2 RCA output interfaces; the front panel has 1 AFC capacitive
- 4. The processor and the digital conference host transmit... — 4. The processor and the digital conference host transmit the conference unit audio signal through the network transmission link. It can receive the digital conference

Technical specifications

Simultaneous turned-on microphone	16 wired mic s + 8 wireless mic s
Frequency response	80Hz ~ 16kHz
SNR	> 75 dB(A)
Dynamic range	>75dB(A)
THD	<0.05%
Main power supply	100-240AC/50-60Hz
Audio output	LINE OUT 1: 1V XLR balanced output ; LINE OUT 2: 1V RCA unbalanced output
Output load	>1KΩ
Static power consumption	3.3W
Connection method	RJ45 network port
Indicator light	AFC function indicator, audio signal indicator, working status indicator, power indicator
Working temperature	-10℃~+60℃
Working humidity	20% □ 80% relative humidity, no condensation
Weight	2.51kg
Dimension (L×W×H)	484×214×44mm
Installation method	19-inch standard cabinet