itc · CONFERENCE & COLUMN LOUDSPEAKERS

TS-403C/TS-603C/TS-803C/TS-1203C

Professional Speaker

The itc TS-403C family is a professional Speaker from itc's Conference & Column Loudspeakers range, built for speech and music reinforcement in conference rooms, banquet halls, theatres, KTV and multipurpose venues. It is offered in 4 versions — TS-403C, TS-603C, TS-803C, TS-1203C — so one design language covers rooms of different sizes.

Key figures: rated power 100W / 200W / 300W / 400W; peak power 200W / 800W / 1200W / 1600W; frequency range 80Hz-20kHz / 80Hz-20kHz / 70Hz-20kHz / 60Hz-20kHz. Highlights include precise vertical directivity, spliced array design and flexible installation.



Key features

- Precise vertical directivity
- Spliced array design
- Flexible installation

Technical specifications

Versions: TS-403C · TS-603C · TS-803C · TS-1203C (values in the same order)

Type	Linear full-range speaker / Column speaker / Column speaker / Column speaker
Rated power	100W / 200W / 300W / 400W
Peak power	200W / 800W / 1200W / 1600W
Max SPL (rated/peak)	108dB / 115dB / 120dB/126dB / 124dB/130dB
Nominal impedance (±20%)	8Ω / 6Ω / 4Ω / 6Ω
Frequency range (-10dB)	80Hz-20kHz / 80Hz-20kHz / 70Hz-20kHz / 60Hz-20kHz
THD	– / 0.293%@265Hz / – / –
Speaker unit	3″×4 / 3″×6 / 3″×8 / 3″×12
Horizontal coverage angle (-6dB)	100° / 110° / 110° / 110°
Vertical coverage angle (-6dB)	90° / 100° / 100° / 100°
Dimensions (H×W×D)	550×152×203mm / 760×152×203mm / 970×152×203mm / 1500×152×203mm
Net weight	6.7kg / 9.8kg / 12.9kg / 20.24kg