itc · CONFERENCE & COLUMN LOUDSPEAKERS

TS-606M/TS-608M

Professional Speaker

The itc TS-606M family is a professional Speaker from itc's Conference & Column Loudspeakers range, built for speech and music reinforcement in conference rooms, banquet halls, theatres, KTV and multipurpose venues. It is offered in 2 versions — TS-606M, TS-608M — so one design language covers rooms of different sizes.

Key figures: rated power 120W / 200W; peak power 480W / 800W; frequency response 70Hz-20KHz / 65Hz-20KHz. Highlights include one mid-woofer and one horn tweeter, strong and wear-resistant cabinet and frequency divider in precise design.



Key features

- One mid-woofer and one horn tweeter
- Strong and wear-resistant cabinet — 15mm plywood housing Wear-resistant spray paint treatment Dust-proof net cotton outside
- Frequency divider in precise design — Optimize the vocal MF performance

Technical specifications

Versions: TS-606M · TS-608M (values in the same order)

Impedance	8Ω
Frequency response	70Hz-20KHz / 65Hz-20KHz
Rated power	120W / 200W
Peak power	480W / 800W
Sensitivity	96dB/W/M / 97dB/W/M
Max SPL(rated/peak)	117dB/123dB / 120dB/127dB
Coverage angle	(H)90° (V)70°
Tweeter	1.3″ tweeter ×1 / 1.3″ tweeter ×1
Woofer	6.5″ woofer ×1 / 8″ woofer ×1
Dimension	350×270×(215+110)mm / 425×340×(275+150)mm
Weight	6.2Kg / 9.2Kg