itc · STAGE MONITORS

TS-610T/TS-612T/TS-615T

Professional Speaker

The itc TS-610T family is a professional Speaker from itc's Stage Monitors range, built for speech and music reinforcement in conference rooms, banquet halls, theatres, KTV and multipurpose venues. It is offered in 3 versions — TS-610T, TS-612T, TS-615T — so one design language covers rooms of different sizes.

Key figures: rated power 300W / 400W / 500W; peak power 1200W / 1600W / 2000W; frequency response 60Hz-20KHz / 50Hz-20KHz / 45Hz-20KHz. Highlights include 15-inch coaxial speaker, compact woofer inverted design, optimized built-in frequency divider and multipurpose structure.



Key features

- 15-inch coaxial speaker — Include a 15-inch woofer and a 75mm tweeter With complete overlapping diffusion of low/high frequency Suitable for semi-reverberation environments
- Compact woofer inverted design — Perfect frequency response, phase response and excellent monitoring capability
- Optimized built-in frequency divider — With abundant sound pressure and comfortable tone
- Multipurpose structure — Support horizontal and vertical placement Used as full-range speaker or stage monitoring speaker
- Durable cabinet with elegant appearance — High-quality birch housing with CNC processing Wear-resisting environment-friendly waterborne paint spray

Technical specifications

Versions: TS-610T · TS-612T · TS-615T (values in the same order)

Impedance	8Ω
Frequency response	60Hz-20KHz / 50Hz-20KHz / 45Hz-20KHz
Rated power	300W / 400W / 500W
Peak power	1200W / 1600W / 2000W
Sensitivity	98dB/W/M / 99dB/W/M / 100dB/W/M
Max SPL(rated/peak)	123dB/129dB / 125dB/131dB / 127dB/133dB
Coverage angle	(H)80° (V)60° / (H)80° (V)60° / (H)90° (V)70°
Tweeter	1.4″ compressed tweeter ×1 / 1.7″ compressed tweeter t×1 / 1.7″ compressed tweeter ×1
Woofer	10″ woofer ×1 / 12″ woofer ×1 / 15″ woofer ×1
Dimension (H×W×D)	340×510×380mm / 380×585×440mm / 395×690×465mm
Weight	17.5Kg / 20.5Kg / 26.5Kg