itc · PAPERLESS CONFERENCE SYSTEMS

TS-8202A

Motorized Paperless Dual-screen Interactive Monitor Lift

The itc TS-8202A is a motorized Paperless Dual-screen Interactive Monitor Lift from itc's Paperless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: touch screen Touch control; screen size 15.6"; screen ratio 16:9. Highlights include with dual-screen design and the machine adopts an all-aluminum structure.



Key features

- With dual-screen design — With dual-screen design, the front 15.6-inch high-definition LCD screen and the rear 11.6-inch vice screen. Working with the paperless conference terminal, it can display the required patterns and
- The integration of the ultra-thin HD touch screen and the… — The integration of the ultra-thin HD touch screen and the lift, no exposed wires and screws, no back boards; the lifting touch screen is neat and beautiful.
- The machine adopts an all-aluminum structure — The machine adopts an all-aluminum structure, high-quality aluminum material and CNC engraving processing treatment; the overall display frame and the cabinet adopt aluminum
- The surface of the machine is anodized and looks bright
- The panel is space-saving with 3mm in thickness and 70mm in… — The panel is space-saving with 3mm in thickness and 70mm in width only. It is only one-third weight of the conventional lift, which reduces transportation cost and the

Technical specifications

Touch screen	Touch control
Lifting time	28S
Elevation angle	0-30°, completely accord with ergonomic principle, without blocking the view and face
Product size	430*70*565mm
Panel size	430*70*3mm
Cabinet size	413.2*59*562mm
Desktop opening size	415.2*61mm (recommended to open hole according to the actual product)
Panel sinking size	431 ×71 ×3mm(recommended to open hole according to the actual product □
Environment condition s	-20℃ □ 50℃, relat ive humidity≤70%
Screen size	15.6"
Screen ratio	16:9
Screen resolution	1920 ×1080
Video port	VGA , HDMI
Back light type	WLED 15K hours, with LED driver
Contrast	800:1
Brightness	300cd/ □

Continued specifications on request.