itc · PAPERLESS CONFERENCE SYSTEMS

TS-8304WC

Paperless Conference Terminal

The itc TS-8304WC is a paperless Conference Terminal from itc's Paperless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: operating system Windows 10 GenuineActivated; cpu Intel Core i5 (six cores) 12 threads, up to 4.4GHz; memory DDR4 8 GB. Highlights include when the conference ends.



Key features

- The multimedia conference terminal controller is equipped… — The multimedia conference terminal controller is equipped with the terminal embedded software to handle the file push, file distribution, browsing and reading, file
- When the conference ends — When the conference ends, the terminal automatically clears the local conference files.
- It has a Type-Cinterface and supports a transmission rate… — It has a Type-Cinterface and supports a transmission rate of up to 10Gbps.
- The device supports one-key restore of the operating system… — The device supports one-key restore of the operating system through physical buttons, which can automatically restore the system to its initial state.
- The device supports one-key restoration of the motherboard… — The device supports one-key restoration of the motherboard configuration through physical buttons to clear user-defined settings and configurations.

Technical specifications

Operating system	Windows 10 GenuineActivated
CPU	Intel Core i5 (six cores) 12 threads, up to 4.4GHz
Memory	DDR4 8 GB
Harddisk	256GB SSD
Network card	2 × Gigabit network card, RJ45 interface
Type-Cinterface	1 × 10G Type-Cport
HDMI output	Support 3840*2160 resolution
VGA output	Support 1920*1080 resolution
One-click restore	1×Recover System One-click Restore
One-click reset	1×Clear CMOS motherboard one-click restoration
Standard interface	2 × USB3.0 , 2 × USB 2.0 , 1 × HDMI , 1 × VGA, 1 × Mic - in port, 1 × Line - Out port , 1 × Line -in port , 1 × COM port , 1 × power port
Self-test light	4 × LED, CPU light red, memory light orange, graphics light white, Boot light green
Work environment	Environment temperature: 0℃ □ 40 ℃; Relative humidity: 10 %~90 % , no condensation
Working power supply	AC 200-240V~,50-60Hz,3A 180W
Power consumption	100W

Continued specifications on request.