itc · PAPERLESS CONFERENCE SYSTEMS

TS-F156MT

Paperless Integrated Lifter (paperless ultra-thin 15.6-inch capacitive

The itc TS-F156MT is a paperless Integrated Lifter (paperless ultra-thin 15.6-inch capacitive LCD screen with microphone lifter, intelligent elevation adjustable 30 degrees) from itc's Paperless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: touch screen Support; screen size 15.6"; screen ratio 16:9. Highlights include adopt an all-aluminum structure.



Key features

- Adopt an integrated lifting design of the ultra-thin HD… — Adopt an integrated lifting design of the ultra-thin HD touch screen and the microphone, no exposed connection wires, no connection backplane, and no exposed screws.
- The integrated lifting design with microphone supports… — The integrated lifting design with microphone supports automatic straightening function; when the microphone pole is bent, it will be automatically straightened when being
- Adopt an all-aluminum structure — Adopt an all-aluminum structure, high-quality aluminum material plus CNC fine carving processing; the screen frame and cabinet are made of aluminum alloy, making the device as a whole delicate
- Adopt anodized treatment, making the surface brighter
- The device panel is only 3mm thick and 70mm wide — The device panel is only 3mm thick and 70mm wide, taking up little space.

Technical specifications

Touch screen	Support
Lift ing time	28S
Elevation angle	0-30°, fully ergonomic, without blocking sight and face
Product size	555*70*650mm
Panel size	555*70*3mm
Cabinet size	538.2*59*647mm
Desktop opening size	540.2*61mm (recommended to open hole according to the actual product)
Panel sink ing size	556*71*3mm (L * W * T) (recommended to open hole according to the actual product)
Environmental conditions	-20℃ □ 50℃, relative humidity≤70%
Screen size	15.6"
Screen ratio	16:9
Screen resolution	1920*1080
Video interface	1 VGA, 1 HDMI
Control interface	1 set of 232/485 input and output interfaces; control the screen lifting and lowering , support hand-in-hand connection; 1 USB port for power on/off, 1 USB port for data transmission
Microphone interface	2 set sof six- pin aviation port s, realize the hand - in - hand connection of multiple units

Continued specifications on request.