itc · PAPERLESS CONFERENCE SYSTEMS

TS-F156ZMT3

Motorized Paperless Interactive Monitor Lift

The itc TS-F156ZMT3 is a motorized Paperless Interactive Monitor Lift from itc's Paperless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: screen Touch control; screen size 15.6 inches; screen ratio 16 □ 9. Highlights include the machine adopts an all-aluminum structure.



Key features

- The machine adopts an all-aluminum structure — The machine adopts an all-aluminum structure, high-quality aluminum material and CNC engraving processing treatment; the overall display frame and the cabinet adopt aluminum
- The surface of the machine is anodized and looks bright
- The panel is space-saving with 3mm in thickness only. It is… — The panel is space-saving with 3mm in thickness only. It is only one-third weight of the conventional lift, which reduces transportation cost and the pressure of conference
- The transmission structure is specially treated to minimize… — The transmission structure is specially treated to minimize the noise; it adopts high-quality stretch-resistant belts, high-precision sliding guide rail and linear bearings,
- Support HDMI and VGA two-channel signal input. When there… — Support HDMI and VGA two-channel signal input. When there is only one signal input, the screen will automatically recognize the signal. When two signals are input at the

Technical specifications

Screen	Touch control
Power supply	AC 220V 50-60/HZ
Lifting time	28S
Elevation angle	30
Product size	430*130*565 mm
Cabinet size	415*126*562mm
Panel size	430*130*3mm
Desktop opening size	417*127mm (recommended to open hole according to the actual product)
Panel sinking size	431*131*3mm □ L*W*T □ (recommended to open hole according to the actual product)
Environment conditions	-20℃ □ 50℃ humidity≤70%
Screen size	15.6 inches
Screen ratio	16 □ 9
Screen resolution	1920*1080 P
Video port	VGA □ HDMI
Video switching	VGA □ HDMI (switch manually)
Screen contrast	500 □ 1
Screen brightness	220cd/ □

Continued specifications on request.