itc · PAPERLESS CONFERENCE SYSTEMS

TS-F215MT3

Motorized Paperless Interactive Monitor Lift



The itc TS-F215MT3 family is a motorized Paperless Interactive Monitor Lift from itc's Paperless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres. It is offered in 66 versions — Model, TS-F215MT3, Touchscreen, Support, Powersupply, AC220V50-60/HZ, Liftingtime, 36S, Elevationangle, 30°, Productsize, 700*77*720mm, Cabinetsize, 685*66*717mm, Panelsize, 700*77*3mm, Desktopopeningsize, 687*68(recommendedtoopenholeaccordingtotheactualproduct), Panelsinkingsize, 701*78*3(L*W*T)(recommendedtoopenholeaccordingtotheactualproduct), Environmentalconditions, -20℃□50℃,relativehumidity≤70%, Screensize, 21.5", Screenratio, 16:9, Screenresolution, 1920(RGB)×1080,FHD, Videointerface, VGA,HDMI, Controlinterface, 1setof232/485inputandoutputinterfaces;controlthescreenliftingandlowering,supporthand-in-handconnection;1USBportforpow Microphoneinterface, 2setsofsix-pinaviationports,realizethehand-in-handconnectionofmultipleunits, Microphonepole, 409mm, Backlighttype, WLED,15Khours,withLEDdriver, Contrast, 1000:1(Typ.)(Transmission), Brightness, 250(Min.), Viewingangle, 85/85/80/80(Typ.)(CR≥10), Signalsystem, LVDS, Totalweight, Netweight:18.9KG;Grossweight:21.3KG, Microphone, Microphonetype, Cardioidpatternelectretmicrophone, Frequencyresponse, 80Hz-16KHz, Inputimpedance, 680Ω, Sensitivity, -41±1.5dB(0dB=1V/Pa,at1KHz), MaxSPL, 120dB, SNR, >80dB, THD, <0.1%, Powerconsumption, 2W, — so one design language covers rooms of different sizes.

Key figures: touch screen Support; screen size 21.5"; screen ratio 16:9. Highlights include adopt an all-aluminum structure.

Key features

- Adopt an integrated lifting design of the ultra-thin HD… — Adopt an integrated lifting design of the ultra-thin HD touch screen and the microphone, no exposed connection wires, no connection backplane, and no exposed screws.
- The integrated lifting design with microphone supports… — The integrated lifting design with microphone supports automatic straightening function; when the microphone pole is bent, it will be automatically straightened when being
- Adopt an all-aluminum structure — Adopt an all-aluminum structure, high-quality aluminum material plus CNC fine carving processing; the screen frame and cabinet are made of aluminum alloy, making the device as a whole delicate
- Adopt anodized treatment, making the surface brighter
- The device panel is only 3mm thick and 77mm wide — The device panel is only 3mm thick and 77mm wide, taking up little space. Its weight is only one third of the conventional lifts, reducing transportation costs and putting less pressure

Technical specifications

Versions: Model · TS-F215MT3 · Touchscreen · Support · Powersupply · AC220V50-60/HZ · Liftingtime · 36S · Elevationangle · 30° · Productsi

Model	TS-F215MT3
Touch screen	Support
Power supply	AC 220V 50-60/HZ
Lift ing time	36 S
Elevation angle	30°

Continued specifications on request.