itc · PAPERLESS CONFERENCE SYSTEMS

TS-FE215MT3

Motorized Paperless Dual-screen Interactive Monitor Lift with Micropho

The itc TS-FE215MT3 is a motorized Paperless Dual-screen Interactive Monitor Lift with Microphone from itc's Paperless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: touch screen Support; screen size 21.5"; screen ratio 16:9. Highlights include adopt a dual-screen design.



Key features

- Adopt an integrated lifting design of the ultra-thin HD... — Adopt an integrated lifting design of the ultra-thin HD touch screen and the microphone, no exposed connection wires, no connection backplane, and no exposed screws.
- Adopt a dual-screen design — Adopt a dual-screen design, 21.5-inch HD LCD front screen, 11.6-inch vice screen, and paperless conference terminal, display the required pictures and participant names, perfectly fulfill the powerful
- The integrated lifting design with microphone supports... — The integrated lifting design with microphone supports automatic straightening function; when the microphone pole is bent, it will be automatically straightened when being
- The screen and the microphone have a separate lifting system — The screen and the microphone have a separate lifting system, and the two can be lifted and lowered separately as needed.
- Adopt an all-aluminum structure — Adopt an all-aluminum structure, high-quality aluminum material plus CNC fine carving processing; the screen frame and cabinet are made of aluminum alloy, making the device as a whole delicate

Technical specifications

Touch screen	Support
Lift ing time	36s
Elevation angle	0-30°, fully ergonomic, without blocking sight and face
Product size	700*77*720mm
Panel size	700*77*3mm
Cabinet size	685*66*717mm
Desktop opening size	687*68 (recommended to open hole according to the actual product)
Panel sink ing size	701*78*3 (L*W*T) (recommended to open hole according to the actual product)
Environmental conditions	-20℃ □ 50℃, relative humidity≤70%
Screen size	21.5"
Screen ratio	16:9
Screen resolution	1920*1080
Video interface	1 VGA, 1 HDMI
Control interface	1 set of 232/485 input and output interfaces; control the screen lifting and lowering , support hand-in-hand connection; 1 USB port for power on/off, 1 USB port for data transmission

Continued specifications on request.