itc · PAPERLESS CONFERENCE SYSTEMS

TS-FE215T

Motorized Paperless Dual-screen Interactive Monitor Lift

The itc TS-FE215T is a motorized Paperless Dual-screen Interactive Monitor Lift from itc's Paperless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: touch screen Touch control; screen size 21.5 inches; screen ratio 16:9. Highlights include with dual-screen design and the machine adopts an all-aluminum structure.



Key features

- The integration of the ultra-thin HD touch screen and the… — The integration of the ultra-thin HD touch screen and the lift, no exposed wires and screws, no back boards; the lifting touch screen is neat and beautiful.
- With dual-screen design — With dual-screen design, the front 21.5-inch high-definition LCD screen and the rear 11.6-inch vice screen. Working with the paperless conference terminal, it can display the required patterns and
- The machine adopts an all-aluminum structure — The machine adopts an all-aluminum structure, high-quality aluminum material and CNC engraving processing treatment; the overall display frame and the cabinet adopt aluminum
- The surface of the machine is anodized and looks bright
- The panel is space-saving with 3mm in thickness and 77mm in… — The panel is space-saving with 3mm in thickness and 77mm in width only. It is only one-third weight of the conventional lift, which reduces transportation cost and the

Technical specifications

Model	TS-FE215T
Touch screen	Touch control
Power supply	AC 220V 50-60/HZ
Power consumption	20W
Lift ing time	36 S
Elevation angle	30
Total weight	12KG
Cabinet size	560*66*647mm
Panel size	582*77*3mm
Lifting window size	499*21.5mm
Desktop opening size	56 2 *68mm (recommended to open hole according to the actual product)
Panel sink ing size	583*78*3mm (recommended to open hole according to the actual product)
Environment condition s	-20℃ □ 50℃ , humidity≤70%
Screen size	21.5 inches
Screen ratio	16:9
Screen resolution	1920*1080
Video interface	VGA, HDMI

Continued specifications on request.