**itc · PAPERLESS CONFERENCE SYSTEMS**

# TS-FZ173T

Motorized Paperless Interactive Monitor Flipper|conference system|pape

The itc TS-FZ173T is a motorized Paperless Interactive Monitor Flipper|conference system|paperless conference system from itc's Paperless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: touch screen Touch control; screen size 17.3"; screen ratio 16:9. Highlights include the machine adopts an all-aluminum structure, multi-point capacitive touch screen and with power protection function.



## Key features

- The machine adopts an all-aluminum structure — The machine adopts an all-aluminum structure, high-quality aluminum material and CNC engraving processing treatment; the overall display frame adopts aluminum alloy and CNC
- The surface of the machine is anodized and looks bright — The surface of the machine is anodized and looks bright, it can adopt sand-blasting, wire-drawing and other treatments and also custom colors.
- Multi-point capacitive touch screen — Multi-point capacitive touch screen, tempered glass, certain resistance to pressure.
- With power protection function — With power protection function, the screen is powered on when turning up, and the screen is powered off when turning down.
- The HD screen is from a well-known Chinese brand — The HD screen is from a well-known Chinese brand; the level A display screen, with high resolution, bright and transparent colors. Resolution: 1920*1080P, aspect ratio: 16:9.

## Technical specifications

| | |
|---|---|
| Model | TS-FZ173T |
| Touch screen | Touch control |
| Elevation angle | 0-60° |
| Chamfer angle | 4*R=10MM |
| Screen size | 17.3" |
| Screen ratio | 16:9 |
| Screen resolution | 1920*1080 |
| Video interface | VGA, HDMI |
| Video switch | VGA, HDMI (switch manually) |
| Contrast | 800:1 |
| Brightness | 300cd/ □ |
| Viewing angle | 89/89/89/89(Typ.) |
| Display thickness | 7.6mm |
| Signal system | EDP |
| Power supply | AC 220V 50-60/HZ |
| Product size | 472*312*130 |

Continued specifications on request.