itc · WIRELESS CONFERENCE SYSTEMS

TS-W326D

Conference Microphone

The itc TS-W326D is a conference Microphone from itc's Wireless Conference Systems range, built for council chambers, boardrooms, government and university meeting halls, courts and conference centres.

Key figures: frequency response 80Hz~16KHz; sensitivity - 40 ±1dB (0dB=1V/Pa,at 1KHz); wireless frequency range 5.15~5.85GHz.



Key features

- All core components of the microphone use domestically… — All core components of the microphone use domestically produced chips, which are safe, confidential, and the core is controllable.
- The microphone adopts a short microphone rod and a… — The microphone adopts a short microphone rod and a high-sensitivity microphone core design, which supports long-distance sound pickup.
- It has intelligent fault detection function to prompt users… — It has intelligent fault detection function to prompt users of AP failure, host communication failure, low signal strength, etc.
- Supports charging via Type-Cport and has intelligent… — Supports charging via Type-Cport and has intelligent indication status.
- SSID can be set via the on-screen interface

Technical specifications

Microphone type	Cardioid directional electret (gold-plated microphone core)
Frequency response	80Hz~16KHz
Microphone input impedance	1KΩ
Sensitivity	- 40 ±1dB (0dB=1V/Pa,at 1KHz)
Maximum SPL	1 20 dB
Signal-to- noise ratio	>80dB(A)
Crosstalk	>70dB
Dynamic range	>80dB
THD	< 0.1 %
Maximum power consumption	2 W
Power supply	21700 lithium battery power supply
Charging method	Connect the charging box to charge via the Type-Cinterface
Color	Graphite gray
Sign-in function	Sign-in via physical silicone button
Display	LCD screen
Installation	Desktop
Wireless frequency range	5.15~5.85GHz

Continued specifications on request.